

TS

Bench scales

Ideal for parcels



LCD indicator in ABS with 100h internal battery duration without interruption



Bench scale





FEATURES:

- Removable indicator.
- Removable support indicator.
- Aluminium load cell.
- 2 versions:
 - Version (P). 400x300 mm. Tubular structure in Epoxy painted steel, stainless steel pan and aluminium load cell, IP65.
 - Version (M). 500x400 mm. Tubular structure in Epoxy painted steel, stainless steel pan and aluminium load cell, IP65.
- ABS indicator, model IB10-S.
- IP54 protection.
- Waterproof keyboard with 5 function keys and ON/OFF keys.
- Backlight LCD display with six 25 mm height digits.
- Backlight of the display with 3 types: automatic, activated and deactivated.
- ABS support for column.
- Operating temperature range: -10°C +40°C.
- Power supply with adaptor AC/DC 240Vac 50Hz.
- Rechargeable internal battery 6V/1.3Ah.
- 100 hours approx. battery life with backlighting on.
- 150 hours approx. battery life without backlighting.
- Programmable gravity.
- Units: g/kg/lb
- RS232 output (PC and print formats).
- Unique range, multi-range or multi-interval.
- Auto switch off (programmable: from 1 to 99 minutes).



Colour-contrast checkweighing function



FUNCTIONS:

- Accumulation
- Totalization
- Piece counting
- Zero
- Hold 4 modes: deactivate, filter for animals, peak value, stable weight and stable weight with auto cancel in zero.
- Control of weight and pieces (limits function) with visual signal and alarm.
- Tare
- Checkweigher

Dimensions (mm)	a	b	c	h
400x300	400	300	440	120
500x400	500	400	540	120

TS SCALES

#Code	Capacity (kg)	Readout (g)	Pan dimensions (mm)	Packing dimensions (mm)	Packing weight (kg)
261376	15	2	400x300	470x555x145	8
261377	30	5	400x300	470x555x145	8
261378	60	10	400x300	470x555x145	8
261379	150	20	400x300	470x555x145	8
261380	30	5	500x400	665x660x145	11,5
261381	60	10	500x400	665x660x145	11,5
261382	150	20	500x400	665x660x145	11,5