

VICON Series

Unique, standard balances for mobile and stationary use





Counting application program



Calibration weights in drawer

Performance features:

- Large amber backlit liquid-crystal display for optimum readability in all ambient conditions
- Intuitive operation with single use tactile keys
- Removable flip-up cover for safe transportation and stockable storage
- Stackable design saves storage
- 5 application programs
- Optional and user installable USB or RS-232 interface kits

Product description:

- Rugged housing made of ABS plastic with maximum overload protection
- Reversible stainless steel weighing pans
- Applications include: Counting with variable reference sample, weighing in percent, display hold, totaling, specific gravity with under-pan weighing
- 14 mass units conversions to choose from with selectable factor
- External "one button" calibration with 3 weight values
- Many models with integrated external weights
- Lock-down capability
- Stainless steel weighing pans
- 9-vilt battery operation (excluding milligram models)
- Glass ring, leveling bubble and adjustable feet included on all milligram models



Adapters: RS-232 and USB data interfaces

Precision balances of the VICON series

Model No.	Capacity	Read- ability	Linearity	Repeat- ability	Pan Size	Calibration Weight	Shipping Weight
VIC-123*	120 g	1 mg	\leq ± 0.003 g	≤± 0.001 g	Ø 97 mm / 3.8"	100 g**	2.3 kg/5.0 lbs
VIC-2mg*	200 g	2 mg	≤± 0.01 g	≤± 0.01 g	Ø 97 mm / 3.8"	100 g**	2.3 kg/5.0 lbs
VIC-303*	300 g	1 mg	≤± 0.004 g	≤± 0.001 g	Ø 97 mm / 3.8"	200 g**	2.4 kg / 5.3 lbs
VIC-4mg*	400 g	2 mg	≤± 0.01 g	≤± 0.01 g	Ø 97 mm / 3.8"	200 g**	2.4 kg / 5.3 lbs
VIC-212	210 g	0.01 g	≤± 0.035 g	≤± 0.01 g	142×130 mm / 5.6×5.1"	200 g**	2.3 kg/5.0 lbs
VIC-412	410 g	0.01 g	≤± 0.03 g	≤± 0.01 g	142×130 mm / 5.6×5.1"	200 g**	2.4 kg/5.3 lbs
VIC-612	610 g	0.01 g	≤± 0.03 g	≤± 0.01 g	142×130 mm / 5.6×5.1"	200 g**	2.4 kg / 5.3 lbs
VIC-511	510 g	0.1 g	≤± 0.2 g	≤± 0.1 g	142×130 mm / 5.6×5.1"	100 g	2.2 kg/4.8 lbs
VIC-711	710 g	0.1 g	≤± 0.2 g	≤± 0.1 g	142×130 mm / 5.6×5.1"	200 g	2.2 kg/4.8 lbs
VIC-1501	1,500 g	0.1 g	≤± 0.2 g	≤± 0.1 g	142×130 mm / 5.6×5.1"	1 kg	2.2 kg/4.8 lbs
VIC-3101	3,100 g	0.1 g	≤± 0.2 g	≤± 0.1 g	142×130 mm / 5.6×5.1"	2 kg	2.2 kg/4.8 lbs
VIC-5101	5,100 g	0.1 g	≤± 0.2 g	≤± 0.1 g	142×130 mm / 5.6×5.1"	5 kg	2.2 kg/4.8 lbs
VIC-4kg	4,100 g	1 g	≤± 1 g	≤± 1 g	142×130 mm / 5.6×5.1"	2 kg	2.2 kg/4.8 lbs
VIC-6kg	6,100 g	1 g	≤± 2 g	≤± 1 g	142×130 mm / 5.6×5.1"	5 kg	2.2 kg/4.8 lbs
VIC-10kg	10,100 g	1 g	≤± 2 g	≤± 1 g	142×130 mm / 5.6×5.1"	5 kg	2.2 kg/4.8 lbs

^{*} Round glass draft shield included

Commonly Used Accessories

Model No.	Description			
YADAP-RS	Adapter with Cable for RS-232 9 pin comport			
YADAP-USB	Adapter with cable for USB comport			
DOTPRINT	Data printer, portable, with cable			
LC-1	Lock-Down Cable and Padlock			

^{**} Calibration weights included